INDUSTRIAL COMPONENT DATA

ICS25-C122X12-9005 1072525 PHOENIX CONTACT DIN rail housing, Upper part, closed, width: 25 mm, height: 122 m..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-C122X12-9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS25-C122X12-9005
Catalog number	1072525
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-7D7BD037BE
Generated	2026-11-19

Product Overview

DIN rail housing, Upper part, closed, width: 25 mm, height: 122 mm, depth: 12 mm, color: black (9005)
Rail box, Top, closed, width: 25 mm, height: 122.5 mm, depth: 14.35 mm, colour: black (Similar RAL 9005)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1072525
Packing unit 1
GTIN 4055626765501
Custom tariff number 85389099
Item properties
Material data
Mechanical strength/tumbling barrel
Test for assessing the risk of fire (glow wire)
General information
Standards and regulations
Dimensions
Ambient conditions
Thermostability (Ball Thrust Test)

Test for substances that would hinder coating with paint or varnish
Packaging information
Classifications
Item properties
Brief article description Upper part of housing
Type ICS25-C122X12-9005
Order No. 1072525
Housing type DIN rail housing
Type Upper part, closed
Max. IP code to attain IP20
Mounting type Snap in
Back to topDimensions
Width [w] 25 mm
Height [h] 122 mm
Depth [d] 12 mm
Back to topMaterial data
Color (RAL) black (9005)
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
Back to topMechanical strength/tumbling barrel
Specification IEC 60068-2-31:2008-05
Height of fall 50 cm
Number of drop cycles 50
Back to topThermostability (Ball Thrust Test)
Specification IEC 60695-10-2:2014-02
Temperature 125 °C
Test duration 1 h
Force 20
Back to topTest for assessing the risk of fire (glow wire)
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Bac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-C122X12-9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.