INDUSTRIAL COMPONENT DATA

# ICS25-F45S-9005 1072519 PHOENIX CONTACT DIN rail housing, ICS filler, closed, width: 25 mm, height: 7 mm, de..

**Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-F45S-9005**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | ICS25-F45S-9005 |
| Catalog number | 1072519 |
| Category | Extruded profile modular housing |
| Minimum order | 10 Pcs |
| Document ID | EO-24124270D1 |
| Generated | 2026-11-19 |

## Product Overview

DIN rail housing, ICS filler, closed, width: 25 mm, height: 7 mm, depth: 45 mm, color: black (9005)
Rail box, ICS plug, closed, width: 25 mm, height: 7.25 mm, depth: 44.9 mm, colour: black (Similar RAL 9005)

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

Key Commercial Data
Orderkey 1072519
Packing unit 1
GTIN 4055626764290
Custom tariff number 85389099
Item properties
Material data
General information
Standards and regulations
Dimensions
Ambient conditions
Packaging information
Classifications
Item properties

Brief article description Connection plate
Type ICS25-F45S-9005
Order No. 1072519
Housing type DIN rail housing
Housing series ICS
Type ICS filler, closed
Mounting type Slot
Ventilation openings present no
Back to topDimensions
Width [ w ] 25 mm
Height [ h ] 7 mm
Depth [ d ] 45 mm
Back to topMaterial data
Color (RAL) black (9005)
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download area.
Back to topPackaging information
Pieces per package 10
Denomination packing units Pcs.
Outer packaging type Resealable bag
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 8.0 27182702
eCl@ss 9.0 27182702
Back to topETIM
ETIM 5.0 EC001031
ETIM 6.0 EC001031
ETIM 7.0 EC001031
Back to top

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-F45S-9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.