INDUSTRIAL COMPONENT DATA

ICS25-TL100X12-9005 1072528 PHOENIX CONTACT DIN rail housing, Upper part, with transparent hinged cover, wid..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-TL100X12-9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS25-TL100X12-9005
Catalog number	1072528
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-E51193C488
Generated	2026-11-19

Product Overview

DIN rail housing, Upper part, with transparent hinged cover, width: 25 mm, height: 100 mm, depth: 12 mm, color: black (9005)
Rail box, Top, with transparent hinged lid, width: 25 mm, height: 101 mm, depth: 14.35 mm, colour: black (Similar RAL 9005)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1072528
Packing unit 1
GTIN 4055626765235
Custom tariff number 85389099
Item properties
Material data
General information
Standards and regulations
Dimensions
Ambient conditions
Packaging information

Classifications
Item properties
Brief article description Upper part of housing
Type ICS25-TL100X12-9005
Order No. 1072528
Housing type DIN rail housing
Type Upper part, with transparent hinged cover
Max. IP code to attain IP20
Mounting type Snap in
Back to topDimensions
Width [w] 25 mm
Height [h] 100 mm
Depth [d] 12 mm
Back to topMaterial data
Color (RAL) black (9005)
Flammability rating according to UL 94 V0
Housing material Polyamide
Back to topAmbient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport) 80 %
Back to topGeneral information
Type of note Assembly instruction:
Note Refer to the data sheet for the range in the download area.
Back to topPackaging information
Type of packaging packed in cardboard
Pieces per package 10
Denomination packing units Pcs.
Outer packaging type Carton
Back to topStandards and regulations
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 5.1 27180505
eCl@ss 6.0 27180800
eCl@ss 7.0 27182702
eCl@ss 8.0 27182702
eCl@ss 9.0 27182702
Back to topETIM
ETIM 5.0 EC001031
ETIM 6.0 EC001031
ETIM 7.0 EC00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-TL100X12-9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.