INDUSTRIAL COMPONENT DATA

IFMC 1,5/ 2-ST-3,5-RN 1844109 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: IFMC 1,5/ 2-ST-3,5-RN



Manufacturer	PHOENIX CONTACT
MPN / Reference	IFMC 1,5/ 2-ST-3,5-RN
Catalog number	1844109
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-2A567E742E
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: IFMC 1.5/.. -ST-RN, pitch: 3.5mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, plug-in system: COMBICON MC 1.5, locking: Socket lock, fixing type: Socket protrusion, packing type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1844109
Packing unit 50 pc
Minimum order quantity 50 pc
GTIN 4046356947459
Weight per Piece (excluding packing) 1.500 g
Custom tariff number 85366990
Country of origin SK (Slovakia)
Item properties
Brief article description Printed-circuit board connector

Plug-in system MINI COMBICON
Type of contact Male connector
Range of articles IFMC 1,5/..-ST-RN
Pitch 3.5 mm
Number of positions 2
Connection method Push-in spring connection
Locking Engagement nose
Number of levels 1
Electrical parameters
Rated current 8 A
Rated insulation voltage (III/2) 160 V
Rated surge voltage (III/2) 2.5 kV
Connection capacity
Conductor cross section solid 0.14 mm² ... 1.5 mm²
Conductor cross section flexible 0.14 mm² ... 1.5 mm²
Conductor cross section AWG / kcmil 24 ... 16
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.14 mm² ... 0.75 mm²
Stripping length 10 mm
Specifications for ferrules
Recommended crimping pliers 1212034 CRIMPFOX 6
Ferrules without insulating collar, according to DIN 46228-1 Cross section: 0.25 mm²; Length: 5 mm ... 7 mm
Cross section: 0.34 mm²; Length: 7 mm
Cross section: 0.5 mm²; Length: 8 mm ... 10 mm
Cross section: 0.75 mm²; Length: 8 mm ... 10 mm
Cross section: 1 mm²; Length: 8 mm ... 10 mm
Cross section: 1.5 mm²; Length: 10 mm
Recommended crimping pliers 1212034 CRIMPFOX 6
Ferrules with insulating collar, according to DIN 46228-4 Cr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IFMC 1,5/ 2-ST-3,5-RN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.