INDUSTRIAL COMPONENT DATA

IB IL AI 4/EF-XC-PAC 2701215 PHOENIX CONTACT Inline terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL AI 4/EF-XC-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL AI 4/EF-XC-PAC
Catalog number	2701215
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-BBCF822DC8
Generated	2026-11-18

Product Overview

Inline terminal
Inline, Analog Input Module, Analog Inputs: 4, 0 V ... 5 V, -5 V ... 5 V, 0 V ... 10 V, -10 V ... 10 V, 0 mA... 20 mA, 4 mA... 20 mA, -20 mA... 20 mA, connection technology: 2, 3, 4 conductors, transmission rate on the local bus: 500 kBit/s, Extreme Conditions variant, protection rating: IP20, including inline connectors and marking fields

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data
Orderkey 2701215
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 160 (C-6-2017)
GTIN 4046356727839
Weight per Piece (excluding packing) 210.000 g
Custom tariff number 85389091
Country of origin DE (Germany)
Note
Utilization restriction 1
Dimensions

Dimensional drawing
Width 48.8 mm
Height 135 mm
Depth 71.5 mm
Note on dimensions Housing dimensions
Ambient conditions
Ambient temperature (operation) -25 °C ... 55 °C (Standard)
-40 °C ... 70 °C (Extended, see section “Tested successfully: use under extreme ambient conditions” in the data sheet.)
Ambient temperature (storage/transport) -40 °C ... 85 °C
Permissible humidity (operation) 10 % ... 95 % (according to DIN EN 61131-2)
Permissible humidity (storage/transport) 10 % ... 95 % (according to DIN EN 61131-2)
Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection IP20
General
Mounting type DIN rail
Net weight 210 g
Note on weight specifications with connectors
Operating mode Process data mode with 5 words/1 word PCP
Interfaces
Designation Inline local bus
Connection method Inline data jumper
Transmission speed 500 kbps
Transmission physics Copper
Inline potentials
Designation Communications power (UL)
Supply voltage 7.5 V DC (via voltage jumper)
Current consumption typ. 85 mA
max. 100 mA
Designation Supply of analog modules (UANA)
Supply voltage 24 V DC
Supply vo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL AI 4/EF-XC-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.