INDUSTRIAL COMPONENT DATA

IB IL 24 PWR IN/2-F-D-PAC 2862152 PHOENIX CONTACT Inline terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL 24 PWR IN/2-F-D-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL 24 PWR IN/2-F-D-PAC
Catalog number	2862152
Category	Fieldbus, decentr. periphery - power supply/segment module
Minimum order	1 Pcs
Document ID	EO-88D747C425
Generated	2026-11-19

Product Overview

Inline terminal
Inline power terminal block, complete with accessories (connector and marking surface), 24 V DC, with fuse (main voltage and segment voltage) and diagnostics

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data
Orderkey 2862152
Packing unit 1 pc
Catalog page Page 135 (C-6-2017)
GTIN 4017918894641
Weight per Piece (excluding packing) 44.000 g
Custom tariff number 85389091
Country of origin DE (Germany)
Note
Utilization restriction 1
Dimensions
Dimensional drawing
Width 12.2 mm

Height 119.8 mm
Depth 71.5 mm
Interfaces
Connection method Inline data jumper
Interface Inline local bus
Power supply
Typical current consumption 30 mA
I/O voltage 24 V DC
I/O voltage range 19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Max. current consumption 4 A
Fuse SI 5 x 20 6, 300 AT (in scope of delivery)
General
Type of protection Surge protection
Reverse polarity protection
Overload protection, short-circuit protection in the main and segment circuits
Weight 59 g
Number of plugs 1
Inline potentials
Designation Communications power (UL)
Supply voltage 7.5 V DC (via voltage jumper)
Current consumption max. 25 mA
Power consumption max. 0.19 W
Designation Main circuit supply (UM)
Supply voltage 24 V DC (via Inline connector)
Supply voltage range 19.2 V ... 30 V (including all tolerances, including ripple)
Power supply unit max. 6.3 A (Sum of UM+ US; 4 A, maximum, when used in potentially explosive areas.)
Current consumption typ. 4 A (nominal value)
Designation Segment circuit supply (US)
Supply voltage 24 V DC
Supply voltage range 19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Power supply unit max. 6.3 A (Sum of UM+ US; 4 A, maximum, when used....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL 24 PWR IN/2-F-D-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.