INDUSTRIAL COMPONENT DATA

PMP-RFID/HF (110X38) 0831028 PHOENIX CONTACT Snap-in markers

Brand: PHOENIX CONTACT | Manufacturer Part Number: PMP-RFID/HF (110X38)



Manufacturer	PHOENIX CONTACT
MPN / Reference	PMP-RFID/HF (110X38)
Catalog number	0831028
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-E31B263D4B
Generated	2026-11-19

Product Overview

Snap-in markers
Snap-in label, with integrated RFID-HF transponder, Mat, white, unlabeled, labelable with: BLUEMARKIDCOLOR, BLUEMARKID, BLUEMARK CLED, mounting class: interlock, usable surface: 110 x 38mm, Number of individual indexes: 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0831028
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 361 (C-3-2017)
GTIN 4046356940580
Weight per Piece (excluding packing) 17.760 g
Custom tariff number 85235200
Country of origin CN (China)
Dimensions
Length (b) 38 mm
Width (a) 110 mm

Ambient conditions
Ambient temperature (operation) -25 °C ... 80 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color white
Components Free from silicone and cadmium
Flammability rating according to UL 94 V0
Material PVC/PC
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 1
Number of individual labels per row 1
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type snapped into marker carrier
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94 V0
Classifications
eCl@ss 10.0.127400629eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss 7.027141137eCl@ss 9.027400629
ETIM 5.0EC000...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PMP-RFID/HF (110X38) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.