INDUSTRIAL COMPONENT DATA

IBS INBC METER/E 2723152 PHOENIX CONTACT Installation remote bus cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: IBS INBC METER/E



Manufacturer	PHOENIX CONTACT
MPN / Reference	IBS INBC METER/E
Catalog number	2723152
Category	Data and communication cable
Minimum order	1 m.
Document ID	EO-62AD95EE3B
Generated	2026-11-18

Product Overview

Installation remote bus cable
By meters, Remote bus installation cable, INTERBUS, shielded, PVC/PVC, black RAL 9005, 9-conductors (3 x 2 x 0.22 mm² + 3 x 1 mm²), color single conductors: green-yellow, white-brown, gray-pink, red, blue, green/yellow, for underground laying

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 2723152
Packing unit 1 M
Note Made to Order (non-returnable)
GTIN 4017918141288
Weight per Piece (excluding packing) 137.600 g
Custom tariff number 85444993
Country of origin DE (Germany)
General data
Number of positions 9
Alternative short product description Installation remote bus cable
Cable

Signal type/category INTERBUS
Cable structure 3 x 2 x 0.22 mm² + 3 x 1 mm²
Conductor cross section 3x 2x 0.22 mm² (Data)
3x 1 mm² (Supply)
Conductor structure signal line 7x 0.20 mm
Conductor structure, voltage supply 14x 0.30 mm
Core diameter including insulation 1 mm (Data)
1.7 mm (Supply)
Wire colors green-yellow, white-brown, gray-pink, red, blue, green/yellow
Twisted pairs 2 cores to the pair
Overall twist 3 pairs and 3 wires to form the core
Shielding Tinned copper braided shield
External sheath, color black RAL 9005
Inner sheath thickness 0.9 mm
External cable diameter D 9.7 mm ±0,3 mm
Minimum bending radius, fixed installation 7.5 x D
Minimum bending radius, flexible installation 15 x D
Outer sheath, material PVC
Material, inner sheath PVC
Material conductor insulation PE
Conductor material Bare Cu litz wires
Insulation resistance >= 5 G?*km (Data)
>= 5 G?*km (Supply)
Loop resistance <= 186.00 ?/km (Data)
<= 19.50 ?/km (Supply)
Cable capacity <= 60 nF/km (At 800 Hz)
Wave impedance 110 ? ±20 ? (at 64 kHz)
95 ? ±15 ? (at >1 MHz)
Near end crosstalk attenuation (NEXT) >= 61 dB (at 772 kHz)
>= 59 dB (with 1 MHz)
>= 55 dB (at 2 ?Hz)
>= 50 dB (at 4 ?Hz)
>= 46 dB (...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IBS INBC METER/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.