INDUSTRIAL COMPONENT DATA

IPC 35 HC/ 3-STF-15,00 BD:1-3 1709944 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: IPC 35 HC/ 3-STF-15,00 BD:1-3



Manufacturer	PHOENIX CONTACT
MPN / Reference	IPC 35 HC/ 3-STF-15,00 BD:1-3
Catalog number	1709944
Category	Cable connector
Minimum order	10 Pcs
Document ID	EO-120D44D4B3
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 35 mm², color: green, nominal current: 125 A, dimensioning voltage (III/2): 1000 V, contact surface: Gold, contact type: Male, Number of potentials: 3, Number of rows: 1, Number of poles per row: 3, number of connections: 3, family of articles: IPC 35 HC/.. -STF, pitch: 15mm, connection type: Screw connection with traction capsule, conductor/printed circuit board connection direction: 0°, Stecksystem: POWER COMBICON 35, Locking: Screw lock, packaging type: boxed
Printed circuit board connector, nominal section: 35 mm2, color: green, nominal current: 125 A, nominal voltage (III/2): 1000 V, contact surface: Ag, contact connection type: Male, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, article family: IPC 35 HC/.. -STF, pitch: 15 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON PC 35, locking: Screw locking, fixing type: Air clamping (screw), packaging type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1709944
Packing unit 1
GTIN 4055626124285

Custom tariff number 85366990
Dimensions
Length [l] 58 mm
Width [w] 46.3 mm
Height [h] 40 mm
Pitch 15 mm
Dimension a 30 mm
General
Range of articles IPC 35 HC/..-STF
Number of positions 3
Connection method Screw connection with tension sleeve
Insulating material group I
Nominal cross section 35 mm²
Flammability rating according to UL 94 V0
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309
ETIM 5.0EC002638ETIM 6.0EC002638
UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IPC 35 HC/ 3-STF-15,00 BD:1-3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.