INDUSTRIAL COMPONENT DATA

# K-8E-M23M8/5,0-H01/M23M8-S4-S 1028582 PHOENIX CONTACT Plug-in connector plastic-coated on both sides

**Brand: PHOENIX CONTACT | Manufacturer Part Number: K-8E-M23M8/5,0-H01/M23M8-S4-S**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | K-8E-M23M8/5,0-H01/M23M8-S4-S |
| Catalog number | 1028582 |
| Category | Power cable less 1 kV, for moving application |
| Minimum order | 10 Pcs |
| Document ID | EO-61DA0CB818 |
| Generated | 2026-11-19 |

## Product Overview

Plug-in connector plastic-coated on both sides
Plastic-coated cable plug, length: 5 m, outer wrap colour: orange RAL 2003
Connector in molded plastic on both sides, cable length: 5 m, shielded: yes, color of outer sheath: orange RAL 2003, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |

## Additional Product Information

Technical dataNotesNotes on operation Observe derating curve.
Safety note
Safety note WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.
• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
• The products are suitable for applications in plant, controller, and electrical device engineering.
• When operating the connectors in outdoor applications, they must be separately protected against environmental

influences.
• Assembled products may not be manipulated or improperly opened.
• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
• When using the product in direct connection with third-party manufacturers, the user is responsible.
• For operating voltages > 50 V AC, conductive connector hou...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / K-8E-M23M8/5,0-H01/M23M8-S4-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.