


INDUSTRIAL COMPONENT DATA

KDS 3-MT BEIGE 1780772 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: KDS 3-MT BEIGE



Manufacturer	PHOENIX CONTACT
MPN / Reference	KDS 3-MT BEIGE
Catalog number	1780772
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-D08B8285D1
Generated	2026-09-29

Product Overview

PCB terminal block

Printed circuit board terminal block, nominal current: 15 A, nominal voltage (III/2): 320 V, nominal cross-section: 2.5 mm², number of potentials: 1, number of rows: 1, number of poles per row: 1, article family: KDS 3-MT, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: beige, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1780772

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918574482

Weight per Piece (excluding packing) 5.740 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [l] 27 mm

Pitch 5.08 mm

Width [w] 5.08 mm

Height 37 mm

Height [h] 40.5 mm

Solder pin [P] 3.5 mm

Hole diameter 1.4 mm

General

Range of articles KDS 3-MT

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 320 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 15 A

Nominal cross section 2.5 mm²

Solder pin surface

Internal cylindrical gage A3

Stripping length 8 mm

Number of positions 1

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 1 mm²

2 conductors with same cross section, stranded min. 0.2 mm²

2 conductors with same cross section, stranded max. 1 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 0.75 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²

2 conductors with same cross sec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / KDS 3-MT BEIGE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.