

INDUSTRIAL COMPONENT DATA

KDS 3-MT GY 1839131 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: KDS 3-MT GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	KDS 3-MT GY
Catalog number	1839131
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-8B448A4778
Generated	2026-09-29

Product Overview

PCB terminal block

Printed circuit board terminal block, nominal current: 15 A, nominal voltage (III/2): 320 V, nominal cross-section: 2.5 mm², number of potentials: 1, number of rows: 1, number of poles per row: 1, article family: KDS 3-MT, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 2, packaging type: boxed. The item can be aligned with different numbers of poles!

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1839131

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4017918228842

Weight per Piece (excluding packing) 5.680 g

Custom tariff number 85369010

Country of origin PL (Poland)

Dimensions

Length [l] 27 mm

Pitch 5.08 mm

Width [w] 5.08 mm

Height 37 mm

Height [h] 40.5 mm

Solder pin [P] 3.5 mm

Hole diameter 1.4 mm

General

Range of articles KDS 3-MT

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 320 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 15 A

Nominal cross section 2.5 mm²

Maximum load current 15 A (with 4 mm² conductor cross section)

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 8 mm

Number of positions 1

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 4 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / KDS 3-MT GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.