
INDUSTRIAL COMPONENT DATA

PTT 2,5-2MT BU 3210265 PHOENIX CONTACT Knife disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTT 2,5-2MT BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTT 2,5-2MT BU
Catalog number	3210265
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-E54FD6D1EA
Generated	2026-11-18

Product Overview

Knife disconnect terminal block
Blade interruptible terminal block, nominal voltage: 400 V, nominal current: 16 A, 1st and 2nd floor, connection type: Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting: NS 35/7.5, NS 35/15, colour: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3210265
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 78 (C-1-2017)
GTIN 4046356863490
Weight per Piece (excluding packing) 17.620 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 2
Number of connections 4

Potentials 2
Nominal cross section 2.5 mm²
Color blue
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Maximum load current 16 A (in case of a 4 mm² conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.)
Nominal current IN 16 A (with 4 mm² conductor cross section)
Nominal voltage UN 400 V
Open side panel Yes
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFP...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTT 2,5-2MT BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.