INDUSTRIAL COMPONENT DATA

UT 4-MT BU 3046278 PHOENIX CONTACT Knife disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-MT BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-MT BU
Catalog number	3046278
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-F893E88B2E
Generated	2026-11-19

Product Overview

Knife disconnect terminal block
Blade interruptible terminal block, nominal voltage: 500 V, nominal current: 20 A, connection type: Screw connection, Dimensioning cross-section: 4 mm², cross-section: 0.14 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, colour: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3046278
Packing unit 50 pc
Catalog page Page 235 (C-1-2017)
GTIN 4017918975616
Weight per Piece (excluding packing) 12.400 g
Custom tariff number 85369010
Country of origin DE (Germany)
General
Number of levels 1
Number of connections 2
Potentials 1
Nominal cross section 4 mm²

Color blue
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.02 W
Maximum load current 20 A (with 6 mm² conductor cross section)
Nominal current IN 20 A (with 4 mm² conductor cross section)
Nominal voltage UN 500 V
Open side panel No
Shock protection test specification IEC 60529:2001-02
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.14 mm² / 0.2 kg
4 mm² / 0.9 kg
6 mm2/ 1.4 kg
Tensile test result Test passed
Conductor cross section tensile test 0.14 mm²
Tractive force setpoint 10 N
Conductor cross section tensile test 4 mm²
Tractive force setpoint 60 N
Conductor cross se...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-MT BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.