INDUSTRIAL COMPONENT DATA

BC 17,8 UT HBUS BK 2896241 PHOENIX CONTACT Mounting base housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: BC 17,8 UT HBUS BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	BC 17,8 UT HBUS BK
Catalog number	2896241
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-AAF1C3F1A9
Generated	2026-11-18

Product Overview

Mounting base housing
Rail box for use in installation distributors according to DIN 43880, Bottom of housing with base anchorage, width: 17.8 mm, height: 89.7 mm, depth: 20.3 mm, color: black (9005), transverse bridging: Rail bus connector (optional), number of poles transverse connector: 16

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2896241
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 698 (C-1-2013)
GTIN 4046356096690
Weight per Piece (excluding packing) 13.240 g
Custom tariff number 85472000
Country of origin DE (Germany)
Item properties
Brief article description Mounting base housing
Type BC 17,8 UT HBUS BK

Order No. 2896241
Housing type Installation component housing
Type Lower part
Dimensions
Width [w] 17.8 mm
Depth [d] 89.7 mm
Material data
Color (RAL) black (9005)
Flammability rating according to UL 94 V0
Housing material Polycarbonate
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Power dissipation, single housing at 20 °C
Ambient temperature 20 °C
Reduction factor 1
Power dissipation, single housing at 30 °C
Ambient temperature 30 °C
Reduction factor 0.84
Power dissipation, single housing at 40 °C
Ambient temperature 40 °C
Reduction factor 0.72
Power dissipation, single housing at 50 °C
Ambient temperature 50 °C
Reduction factor 0.6
Power dissipation, single housing at 60 °C
Ambient temperature 60 °C
Reduction factor 0.48
Packaging information
Pieces per package 10
Denomination packing units Pcs.
Standards and regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BC 17,8 UT HBUS BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.