INDUSTRIAL COMPONENT DATA

ME 45 UT/FE BUS/ 5 GN 2709765 PHOENIX CONTACT Mounting base housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 45 UT/FE BUS/ 5 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME 45 UT/FE BUS/ 5 GN
Catalog number	2709765
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-4EB44ECFF9
Generated	2026-11-18

Product Overview

Mounting base housing
Rail box, Lower part of the housing with metal pin, with 2 FE contacts, high design, with ventilation slits, width: 45.2 mm, height: 99 mm, depth: 107.3 mm, color: green (6021), cross bridge: integrated bus connector, number of poles cross connector: 5, Bus connector: 5 parallel contacts
DIN rail enclosures, enclosure base with metal mounting foot, with 2 FE contacts, high type, with ventilation slots, width: 45.2 mm, height: 99 mm, depth: 107.3 mm, colour: green (similar to RAL 6021), cross connection: integrated bus connector, no. of poles cross connector: 5, Bus connector: 5 parallel contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2709765
Packing unit 10 pc
Note Made to Order (non-returnable)
Catalog page Page 664 (C-1-2013)
GTIN 4017918886998
Weight per Piece (excluding packing) 73.510 g
Custom tariff number 85369010
Country of origin DE (Germany)

General
Housing type Component housing
Housing material Polyamide
Color (RAL) green
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Dimensions
Length 99 mm
Height 114.5 mm
Width 45 mm
Depth 99 mm
Technical data
Connection in acc. with standard CUL
Nominal voltage UN 300 V
Nominal current IN 8 A
Indicator1 CUL1
Power dissipation without gap 8.2 W
Power dissipation with 20 mm gap 16.5 W
Number of positions 32
8
Standards and Regulations
Connection in acc. with standard CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC001031ETIM 5.0EC001031ETIM 6.0EC001031
UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC 13.231261501

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 45 UT/FE BUS/ 5 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.