INDUSTRIAL COMPONENT DATA

LPC 6/ 2-STL2-7,62 1716930 PHOENIX CONTACT Connector for printed circuit board, nominal current: 41 A, numbe..

Brand: PHOENIX CONTACT | Manufacturer Part Number: LPC 6/ 2-STL2-7,62

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	LPC 6/ 2-STL2-7,62
Catalog number	1716930
Category	Cable connector
Minimum order	25 Pcs
Document ID	EO-5A8F0D4090
Generated	2026-11-18

Product Overview

Connector for printed circuit board, nominal current: 41 A, number of poles: 2, pitch: 7.62 mm, Connection type: spring clamp push-in, color: green, surface contacts: Tin
Connector for printed circuit board, nominal section: 6 mm², color: green, nominal current: 41 A, nominal voltage (III/2): 1000 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: LPC 6/.. -STL, pitch: 7.62 mm, connection type: Push-in lever connection, driver/printed circuit board connection direction: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON PC 6, locking: Snap lock, fixing type: Lace flange, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LPC 6/ 2-STL2-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.