INDUSTRIAL COMPONENT DATA

LS-WMTB-V4A (D50) 1099826 PHOENIX CONTACT Cable marker, Stainless steel label, silver, unlabeled, can be lab..

Brand: PHOENIX CONTACT | Manufacturer Part Number: LS-WMTB-V4A (D50)



Manufacturer	PHOENIX CONTACT
MPN / Reference	LS-WMTB-V4A (D50)
Catalog number	1099826
Category	Cable coding system
Minimum order	5 Pcs
Document ID	EO-31FA61D289
Generated	2026-11-18

Product Overview

Cable marker, Stainless steel label, silver, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, mounting type: Assembly with cable binders, cable diameter: > 2.9 mm, lettering field size: d 50 mm, Number of individual labels: 9
Cable marker, Stainless steel plate, silver, unlabeled, labelable with: TOPMARKNEO, TOPMARK LASER, mounting class: Mounting with cable tie, cable diameter: > 2.9 mm, useful surface: 44x22mm, Number of individual indexes: 9
Cable marker, Stainless steel label, silver, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, mounting type: Assembly with cable ties, cable diameter: > 2.9 mm, Number of individual labels: 9, text field height: 22 mm, text field width: 44 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking
Type circular
Type Laser sheet
Data management status
Article revision 00
Marking
Number of individual labels 9
Identification technology Direct laser marking
DimensionsWidth 50 mm

Text field width 44.00 mm
Text field height 22.00 mm
Length 50 mm
Hole diameter 5.00 mm
Material strength 0.50 mm
External dimensions
Outside diameter 1 mm ... 136 mm
Material specificationsColor Steel/stainless steel color
Material V4A (1.4404; AISI 316L)
Components free from silicone, halogen, and cadmium
Cable/lineExternal cable diameter > 2.90 mm
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
Test for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Specification IEC 60068-2-2:2007-07
Result Test passed
Duration 240 h
Temperature for testing 350 °C
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 225 °C (250 °C) Test passed
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-1):2011-07
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl
[CAS No...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LS-WMTB-V4A (D50) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.