INDUSTRIAL COMPONENT DATA

CTM 1X2-110AC 2838539 PHOENIX CONTACT Surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: CTM 1X2-110AC



Manufacturer	PHOENIX CONTACT
MPN / Reference	CTM 1X2-110AC
Catalog number	2838539
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-42B301A0D4
Generated	2026-11-18

Product Overview

Surge protection plug
LSA-PLUS (COMTRAB CTM) connector for potential-free signal circuits, to protect a two-wire cable circuit of analogue and digital telecommunication interfaces (up to 50 MBits/s). Rated voltage: 110 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2838539
Packing unit 10 pc
Catalog page Page 166 (C-4-2017)
GTIN 4017918819569
Weight per Piece (excluding packing) 9.900 g
Custom tariff number 85363010
Country of origin DE (Germany)
Dimensions
Height 21 mm
Width 9.4 mm
Depth 52.4 mm
Ambient conditions

Ambient temperature (operation) -25 °C ... 75 °C
Altitude <= 2000 m (amsl (above mean sea level))
Degree of protection IP20
General
Housing material PA 6.6
Flammability rating according to UL 94 V-0
Color jet black RAL 9005
Overvoltage category II
Degree of pollution 2
Mounting type On CT-TERMIBLOCK and LSA-PLUS disconnect strip
Type LSA-PLUS module
Direction of action Line-Line & Line-Earth Ground
Arrester can be tested with CHECKMASTER from software version: From SW rev. 1.10
Transmission speed 42 Mbps
Protective circuit
IEC test classification B2
C1
C2
C3
D1
Nominal voltage UN 110 V AC
Maximum continuous voltage UC 60 V DC
125 V AC
Rated current 380 mA AC (25 °C)
150 mA DC (25 °C)
Operating effective current ICat UC <= 5 µA (in the signal circuit)
Residual current IPE <= 2 µA (per path)
Nominal discharge current In(8/20) µs (line-line) 5 kA
Nominal discharge current In(8/20) µs (line-earth) 5 kA
Pulse discharge current Iimp(10/350) µs (line-earth) 1 kA
Total discharge current Itotal(8/20) µs 10 kA
Total discharge current Itotal(10/350) µs 2.5 kA
Nominal pulse current Ian (10/1000) µs (line-line) 100 A
Nominal pulse current Ian (10/1000) µs (line-earth) 100 A
Output voltage limitation at 1 kV/µs (...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CTM 1X2-110AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.