

INDUSTRIAL COMPONENT DATA

CTM 2X1-180DC-GS-P 2838623 PHOENIX CONTACT Surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: CTM 2X1-180DC-GS-P



Manufacturer	PHOENIX CONTACT
MPN / Reference	CTM 2X1-180DC-GS-P
Catalog number	2838623
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-13C825D322
Generated	2026-09-19

Product Overview

Surge protection plug

LSA-PLUS (COMTRAB CTM) plug-in protection with Powercross protection and sufficient surge protection for 2 signal conductors. Rated voltage: 180 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2838623

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 167 (C-4-2017)

GTIN 4017918948375

Weight per Piece (excluding packing) 8.340 g

Custom tariff number 85363010

Country of origin DE (Germany)

Dimensions

Height 21 mm

Width 9.5 mm

Depth 53.5 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Degree of protection IP20

General

Housing material PA

Flammability rating according to UL 94 V-0

Color black

Standards for clearances and creepage distances DIN VDE 0110-1

IEC 60664-1

Overvoltage category II

Degree of pollution 2

Mounting type On CT-TERMIBLOCK and LSA-PLUS disconnect strip

Type LSA-PLUS module

Direction of action Line-Line & Line-Earth Ground

Arrester can be tested with CHECKMASTER from software version: From SW rev. 2.20

Near-end crosstalk attenuation aN between adjacent articles 70 dB (up to 1 MHz 100 ? system)

50 dB (up to 10 MHz 100 ? system)

30 dB (up to 100 MHz, 100 ? system)

Protective circuit

IEC test classification A2

B1

B2

B3

C1

C2

C3

D1

D2

VDE requirement class A2

B1

B2

B3

C1

C2

C3

D1

D2

Nominal voltage UN 180 V DC

Maximum continuous voltage UC $\pm$ 180 V DC

Rated current 120 mA (25 °C)

Operating effective current ICat UC $\leq$ 2 μ A

Residual current IPE $\leq$ 2 μ A

Nominal discharge current In(8/20) μ s (line-earth) 5 kA

Pulse discharge current Iimp(10/350) μ s 1 kA

Total discharge current Itotal(8/20) μ s 10 kA

Total discharge current Itotal(10/350) μ s 2.5 kA

Max. discharge current Imax(8/20) μ s maxi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CTM 2X1-180DC-GS-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.