INDUSTRIAL COMPONENT DATA

M23-12P2N12W500S 1543918 PHOENIX CONTACT M23, Conect. plug. to be apar. front wall, series: M23 PRO Signal, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: M23-12P2N12W500S



Manufacturer	PHOENIX CONTACT
MPN / Reference	M23-12P2N12W500S
Catalog number	1543918
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-D847061D8E
Generated	2026-11-19

Product Overview

M23, Conect. plug. to be apar. front wall, series: M23 PRO Signal, straight, shielded: yes, for quick ONECLICK and standard lock, No. of poles: 12, Direction of rotation: Opposite movement, type of contact connection: Male, Solder connection, 4x Ø 3.2, flange measurement: 26 mm x 26 mm, coding: N, The item does not contain lead according to the RoHS II directive without exception 6c (Pb&lt.; 0.1 %)
M23, Conect. plug. for apar. wall front, M23 PRO, straight, for ONECLICK quick lock and standard, No. of poles: 12, Direction of rotation: Counter movement, contact type: Male, Weld connection, 4x Ø 3.2, flange size: 26mm x 26mm, coding: N, The article does not contain lead according to the RoHS II directive without the exception 6c (Pb< 0.1%)
M23, Device connector front mounting, series: M23 PRO Signal, straight, for standard and ONECLICK fast locking system, No. of pos.: 12, Direction of rotation: Counter direction, contact connection type: Pin, Solder connection, 4x Ø 3.2, flange dimensions: 26 mm x 26 mm, coding: N, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesGeneral Please observe the derating curve.
Safety note
Safety note WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.

• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
• The products are suitable for applications in plant, controller, and electrical device engineering.
• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
• Assembled products may not be manipulated or improperly opened.
• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
• When using the product in direct connection with third-party manufacturers, the user is responsible.
• For operating voltages > 50 V AC, conductive connector hou...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / M23-12P2N12W500S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.