INDUSTRIAL COMPONENT DATA

M23-7EP198AA600S 1628484 PHOENIX CONTACT Device connector for front wall, M23 PRO, angled rotatable, for sta..

Brand: PHOENIX CONTACT | Manufacturer Part Number: M23-7EP198AA600S



Manufacturer	PHOENIX CONTACT
MPN / Reference	M23-7EP198AA600S
Catalog number	1628484
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-60862D5CB5
Generated	2026-11-19

Product Overview

Device connector for front wall, M23 PRO, angled rotatable, for standard and ONECLICK fast locking system, M23, No. of pos.: 4+3+PE, type of contact: Pin, Crimp connection, flange dimensions: 28 mm x 28 mm
M23, Conect. plug. to be apar. front wall., M23 PRO, Swivel elbow, for quick ONECLICK and standard lock, No. of poles: 4+3+PE, contact type: Male, Crimped connection, flange measurement: 28 mm x 28 mm, The item does not contain lead according to the RoHS II directive without the exception 6c (Pb< 0.1%)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1628484
Packing unit 1 pc
Catalog page Page 147 (C-2-2019)
GTIN 4055626622156
Weight per Piece (excluding packing) 120.000 g
Custom tariff number 85366990
Country of origin DE (Germany)
Drawings
Data of the insulating body
Environmental Product Compliance

Temperature range
Housing data
Classifications
Drawings
Dimensional drawing
Technical drawings can be found under Downloads
Dimensional drawing
Installation dimensions
Schematic diagram
Back to topTemperature range
Ambient temperature (operation) -40 °C ... 125 °C
Back to topData of the insulating body
Note Order information: Order crimp contacts 4 x Ø 1 mm, 4 x Ø 2 mm separately
Insulator material PA 6.6
Contact connection method Crimp connection
Type of contacts Pin
Application Power
Number of positions 8
Contact diameter of power contacts 2 mm
Litz wire cross section of power contacts min. 0.25 mm²
Litz wire cross section of power contacts max. 4 mm²
Rated current for power contacts 30 A
Additional text for max. connection cross section
Rated voltage of power contact 630 V
Rated surge voltage 6 kV
Overvoltage category III
Degree of pollution 3
Contact diameter of signal contacts 1 mm
Litz wire cross section of signal contacts min. 0.06 mm²
Litz wire cross section of signal contacts max. 1 mm²
Rated current of each signal contact at 25°C 9 A
Additional text for max. connection cross section
Rated voltage of signal contact 250 V
Rated surge voltage 4 kV
Overvoltage category III
Degree of pollut...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / M23-7EP198AA600S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.