INDUSTRIAL COMPONENT DATA

MACX MCR-RTD-I 1050192 PHOENIX CONTACT Temperature transducer, converts signals from resistance temperature ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MACX MCR-RTD-I



Manufacturer	PHOENIX CONTACT
MPN / Reference	MACX MCR-RTD-I
Catalog number	1050192
Category	Temperature transformer
Minimum order	1 Pcs
Document ID	EO-F5D6E87BCE
Generated	2026-11-19

Product Overview

Temperature transducer, converts signals from resistance temperature detectors and resistors into analog 0/4 - 20 mA signals. Freely programmable, screw connection, SIL, 3-way electrical isolation, standard configuration.
Temperature converter, transforms signals from heat resistors and resistors into analog signals of 0/4-20 mA. Free programmable, screw connection, safety integrity level, 3-way galvanic separation, standard configuration.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 1050192
Packing unit 1 pc
Catalog page Page 130 (C-5-2019)
GTIN 4055626666105
Weight per Piece (excluding packing) 0.000 g
Custom tariff number 85437090
Country of origin DE (Germany)
Drawings
Dimensions
Input data
Power supply

EMC data
Environmental Product Compliance
Note
Ambient conditions
Output data
General
Standards and Regulations
Classifications
Drawings
Block diagram
Pictogram
Back to topNote
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Back to topDimensions
Width 12.5 mm
Height 112.5 mm
Depth 114.5 mm
Back to topAmbient conditions
Ambient temperature (operation) -40 °C ... 70 °C (Any mounting position)
Ambient temperature (storage/transport) -40 °C ... 80 °C
Permissible humidity (operation) 5 % ... 95 % (non-condensing)
Noise immunity EN 61000-6-2 When being exposed to interference, there may be minimal deviations.
Back to topInput data
Sensor types (RTD) that can be used Pt, Ni, Cu sensors: 2, 3, 4-wire
Temperature measuring range -200 °C ... 850 °C (Range depending on the sensor type)
Input signal range 0 ? ... 50 k?
Potentiometer resistance range 0 ? ... 50 k?
Cable resistance <= 50 ? per cable
Sensor input current 10 µA ... 210 µA (up to 2 x 210 µA for 3-conductor)
Measuring range span >= 50 K
Back to topOutput data
Signal output Current output
Configurable/programmable Yes
Current output signal 0 mA ... 20 mA
4 mA ... 20 mA (SIL)
Max. current output signal >= 21 mA
Load/output load....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MACX MCR-RTD-I with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.