INDUSTRIAL COMPONENT DATA

FL SWITCH 3008T 2891035 PHOENIX CONTACT Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 3008T



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 3008T
Catalog number	2891035
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-E6B7FBCB4B
Generated	2026-11-18

Product Overview

Industrial Ethernet Switch
Ethernet managed switch with eight RJ45 ports for 10/100 MBit/s and an operating temperature of -40 °C ... +75 °C
Managed Ethernet switch with eight RJ45 ports at 10/100 Mbps and operating temperature of -40°C ... +75°C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Technical dataDimensionsDimensional drawing
Width 54.4 mm
Height 146.4 mm
Depth 125 mm
NotesNote on application
Note on application Only for industrial use
Utilization restriction
EMC note EMC: class A product, see manufacturer's declaration in the download area
Utilization restriction
CCCex note Use in potentially explosive areas is not permitted in China.
Material specificationsHousing material Aluminum
MountingMounting type DIN rail mounting
InterfacesEthernet (RJ45)

Connection method RJ45
Note on the connection method Auto negotiation and autocrossing
Transmission speed 10/100 Mbps
Transmission physics Ethernet in RJ45 twisted pair
Transmission length 100 m
No. of channels 8 (RJ45 ports)
Product propertiesProduct type Switch
Product family Managed Switch 3000
Type Block design
MTTF 35.9 Years (MIL-HDBK-217F standard, temperature 25°C, operating cycle 100%)
Data management status
Article revision 10
Insulation characteristics
Protection class III (VDE 0106, IEC 60536)
Switch functions
Basic functions Store and forward switch, Extended Ring and IEEE redundancy, Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP, web customization, user accounts
Signal contact control voltage 24 V DC
Signal contact control current 100 mA
Redundancy ERR (Extended ring redundancy)
Status and diagnostic indicators LEDs: US1, US2(redundant voltage supply), link and activity per port
Security functions
Basic functio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 3008T with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.