INDUSTRIAL COMPONENT DATA

US-PML-M100 (D50) 1014176 PHOENIX CONTACT Mandatory sign

Brand: PHOENIX CONTACT | Manufacturer Part Number: US-PML-M100 (D50)



Manufacturer	PHOENIX CONTACT
MPN / Reference	US-PML-M100 (D50)
Catalog number	1014176
Category	Warning/signing plate
Minimum order	10 Pcs
Document ID	EO-4437DDEC06
Generated	2026-11-19

Product Overview

Mandatory sign
Obligation plate, Card, blue/white, unlabeled, labelable with: THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting class: glued, diameter: 50 mm, useful surface: d: 50mm, Number of individual indexes: 4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 1014176
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 374 (C-3-2017)
GTIN 4046356786447
Weight per Piece (excluding packing) 5.370 g
Custom tariff number 39199080
Country of origin DE (Germany)
Dimensions
Width (a) 0 mm
Height (c) 0 mm

Diameter 50.00 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 90 °C
Ambient temperature (assembly) > 8 °C
Recommended storage conditions 4°C - 40°C
Storage in the original packaging is recommended.
General
Color blue/white
Type Round
Components Silicone-free
Material PVC
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Printing Blank
Number of individual labels 4
Adhesive Acrylic
Printability Thermal transfer
Device 5148888 THERMOMARK PRIME
Ink ribbon 0803376 TMP-RIBBON 110 WH 100
Test specification weathering-resistance Following ISO 4892-2:2013-03
Procedure
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Procedure A
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification following DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 50 µm
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Environmental Product Complia...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-PML-M100 (D50) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.