INDUSTRIAL COMPONENT DATA

SK 3,8 REEL P6,2 WH CUS 0825126 PHOENIX CONTACT Marker card

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK 3,8 REEL P6,2 WH CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SK 3,8 REEL P6,2 WH CUS
Catalog number	0825126
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-8B4BB3A296
Generated	2026-11-19

Product Overview

Marker card
Strip card, available: per card, white, labelled according to customer specifications, mounting type: glued, for terminal width: 6.2 mm, usable surface: endless x 3.8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0825126
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 103 (C-5-2013)
GTIN 4046356355094
Weight per Piece (excluding packing) 1.040 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Width (a) 3.8 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 150 °C

Ambient temperature (assembly) > 15 °C
Recommended storage conditions 23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing.
General
Note Marking up to max. 25-pos.
Color white
Type adhesive
Components free from silicone and halogen
Material Polyester
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of marker strips 12
Adhesive Acrylic
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146231 THERMOMARK X1.2
Ink ribbon 5145384 THERMOMARK-RIBBON 110
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 53 µm
Adhesive strengt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK 3,8 REEL P6,2 WH CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.