INDUSTRIAL COMPONENT DATA

SK 5,08/3,8:UNBEDRUCKT 0805412 PHOENIX CONTACT Marker card

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK 5,08/3,8:UNBEDRUCKT



Manufacturer	PHOENIX CONTACT
MPN / Reference	SK 5,08/3,8:UNBEDRUCKT
Catalog number	0805412
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-429934C171
Generated	2026-11-19

Product Overview

Marker card
Strip card, white, unlabeled, labelable with: Special marker: without printing, mounting class: glued, for terminal width: 5.08 mm, useful surface: 5.08 x 3.8 mm, Number of individual indexes: 120

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0805412
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 502 (CL-2009)
GTIN 4017918129170
Weight per Piece (excluding packing) 0.730 g
Custom tariff number 39199080
Country of origin PL (Poland)
Dimensions
Width (a) 5.08 mm
Height (c) 3.8 mm
Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C
Ambient temperature (assembly) > 15 °C
Recommended storage conditions 23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing.
General
Note Can be labeled with CMS
Color white
Type adhesive
Components free from silicone and halogen
Material Polyester
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of marker strips 12
Adhesive Acrylic
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146231 THERMOMARK X1.2
Ink ribbon 5145384 THERMOMARK-RIBBON 110
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 53 µm
Adhesive...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK 5,08/3,8:UNBEDRUCKT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.