INDUSTRIAL COMPONENT DATA

SK U/3,8 WH:UNBEDRUCKT 0803906 PHOENIX CONTACT Marker card

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK U/3,8 WH:UNBEDRUCKT



Manufacturer	PHOENIX CONTACT
MPN / Reference	SK U/3,8 WH:UNBEDRUCKT
Catalog number	0803906
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-87A2D1DCBD
Generated	2026-11-19

Product Overview

Marker card
Strip card, DIN A4, white, unlabelled, labelled with: PLOTMARK, CMS-P1-PLOTTER, Office printing systems, mounting class: glued, for terminal width: 210 mm, usable surface: 186 x 3.8 mm, Number of individual indexes: 1440
Marking card, Din A4, white, blank, can be labelled with: PLOTMARK, CMS-P1-PLOTTER, Office printing systems, mounting type: glue, for clamp thickness: 210 mm, Number of individual tags: 1440, height of the text field: 3.8 mm, width of the text field: 186 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0803906
Packing unit 10 pc
Note Made to Order (non-returnable)
Catalog page Page 159 (C-3-2017)
GTIN 4017918007799
Weight per Piece (excluding packing) 13.130 g
Custom tariff number 39199080
Country of origin DE (Germany)
Dimensions

Length (b) 186 mm
Width (a) 3.8 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 150 °C
Ambient temperature (assembly) > 0 °C
Recommended storage conditions 20-25 °C / 40-50 % relative humidity.
General
Note Print image may vary depending on laser printer
Color white
Type adhesive
Components free from silicone and halogen
Material Polyester
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 1440
Number of individual labels per row 36
Number of marker strips 40
Adhesive Acrylic
Printability Office printing systems
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 50 µm
Adhesive strength 20 µm
Marking mounting type adhesive
S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK U/3,8 WH:UNBEDRUCKT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.