INDUSTRIAL COMPONENT DATA

SK U/5,0 WH:UNBEDRUCKT 0803922 PHOENIX CONTACT Marker card

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK U/5,0 WH:UNBEDRUCKT



Manufacturer	PHOENIX CONTACT
MPN / Reference	SK U/5,0 WH:UNBEDRUCKT
Catalog number	0803922
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-2E738CFF4E
Generated	2026-11-18

Product Overview

Marker card
Strip card, DIN A4, white, unlabelled, labelled with: PLOTMARK, CMS-P1-PLOTTER, Office printing systems, mounting type: glued, for terminal width: 210 mm, usable surface: 186 x 5 mm, Number of individual indexes: 630
Marker card, Din A4, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, Office printing systems, mounting type: adhesive, for terminal block width: 210 mm, Number of individual labels: 630, text field height: 5 mm, text field width: 186 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataNotesGeneral Print image may vary depending on laser printer
Product propertiesProduct type Terminal marking
Pitch 210 mm
Type Label
Data management status
Article revision 07
Marking
Number of individual labels 630
Number of individual labels per row 18
Number of marker strips 35

Identification technology Office laser printing
DimensionsText field width 186.00 mm
Height 5 mm
Text field height 5.00 mm
Length 186 mm
Pitch 210 mm
Material specificationsFoil strength 50 µm
Adhesive strength 20 µm
Adhesive Acrylic
Color white (RAL 9010)
Material Polyester
Components free from silicone and halogen
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 200 °C (230 °C) Test passed
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-01):2020-03
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl
[CAS No. 67-63-0] Test passed
n-Hexane
[CAS No. 110-54-3] Test passed
Water + Petroleum ether
[CAS No. 64742-82-1] Test passed
Sodium hydroxide 0.1 mol/l
[CAS No. 1310-73-2] Tes...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK U/5,0 WH:UNBEDRUCKT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.