INDUSTRIAL COMPONENT DATA

# UCT-EM (30X5) 0801505 PHOENIX CONTACT Marker for end clamp

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-EM (30X5)**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UCT-EM (30X5) |
| Catalog number | 0801505 |
| Category | Labelling for terminal block |
| Minimum order | 10 Pcs |
| Document ID | EO-078E6246BD |
| Generated | 2026-11-18 |

## Product Overview

Marker for end clamp
Marker for final support, Mat, white, unlabeled, labelable with: TOPMARKNEO, TOPMARK LASER, BLUEMARKIDCOLOR, BLUEMARKID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting class: interlock, useful surface: 30x5mm, Number of individual indexes: 24

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > MS Material |

## Additional Product Information

Key Commercial Data
Orderkey 0801505
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 160 (C-3-2017)
GTIN 4046356673525
Weight per Piece (excluding packing) 11.000 g
Custom tariff number 39269097
Country of origin PL (Poland)
Dimensions
Length (b) 30 mm
Width (a) 5 mm

Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
General
Color white
Components free from silicone and halogen
Flammability rating according to UL 94 V0
Material PC
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 24
Number of individual labels per row 8
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions IEC 61010-1:2010-06
Result Test passed
Marking mounting type snapped into marker carrier
Result Test passed
Oxygen index (DIN EN ISO 4589-2) 32.4 %
R22 HL 1 - HL 3
R23 HL 1 - HL 3
R24 HL 1 - HL 3
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94 V0
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R2...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-EM (30X5) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.