INDUSTRIAL COMPONENT DATA

UC-TMN 5,2 0822945 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-TMN 5,2



Manufacturer	PHOENIX CONTACT
MPN / Reference	UC-TMN 5,2
Catalog number	0822945
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-2B71161D95
Generated	2026-11-18

Product Overview

Marker for terminal blocks
Marker for terminals, Mat, white, unlabeled, labelable with: BLUEMARKIDCOLOR, BLUEMARKID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting class: interlock, for terminal width: 5.2 mm, useful surface: 3.97 x 4.6 mm, Number of individual indexes: 96

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0822945
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 122 (C-3-2017)
GTIN 4046356332422
Weight per Piece (excluding packing) 7.100 g
Custom tariff number 39269097
Country of origin PL (Poland)
Dimensions
Length (b) 3.97 mm
Width (a) 4.6 mm

Height (c) 4 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
General
Color white
Type other
Components free from silicone and halogen
Flammability rating according to UL 94 V2
Material PA
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 96
Number of individual labels per row 12
Printability UV LED technology
Plotter
Device 5147999 BLUEMARK CLED
5144615 CMS-P1-PLOTTER
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type Plug in
Result Test passed
Oxygen index (DIN EN ISO 4589-2) 28,2%
Class I 3
Class F 2
R22 HL 1 - HL 2
R23 HL 1 - HL 2
R24 HL 1 - HL 2
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94 V2
Fire protection for rail vehicles (DIN EN 45545-2)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC-TMN 5,2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.