
INDUSTRIAL COMPONENT DATA

UCT-TMF 10 YE 0829207 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-TMF 10 YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT-TMF 10 YE
Catalog number	0829207
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-2944C68994
Generated	2026-11-18

Product Overview

Marker for terminal blocks
Marker for terminals, Mat, yellow, unlabeled, labelable with: TOPMARKNEO, TOPMARK LASER, BLUEMARKIDCOLOR, BLUEMARKID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting class: interlock, for terminal width: 10.2 mm, useful surface: 9.4 x 4.7 mm, Number of individual indexes: 36

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0829207
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 143 (C-3-2017)
GTIN 4046356563086
Weight per Piece (excluding packing) 9.100 g
Custom tariff number 39269097
Country of origin DE (Germany)
Dimensions
Length (b) 5 mm

Width (a) 9.6 mm
Height (c) 1.64 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
General
Note Can be labeled via thermal transfer
Color yellow
Type flat
Components free from silicone and halogen
Flammability rating according to UL 94 V0
Material PC
PC
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 36
Number of individual labels per row 6
Printability Thermal transfer
Inkjet printing
Device 5146464 THERMOMARK CARD
5146563 THERMOMARK CARD-UCT-MAG2
5147888 BLUEMARK LED
5147999 BLUEMARK CLED
Ink ribbon 0801371 THERMOMARK-RIBBON 110-TC
5147421 BLUEMARK FLUID-CARTRIDGE
5146662 BLUEMARK CLED-FLUID-CARTR.
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type snap into flat marker groove
Result Test p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-TMF 10 YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.