INDUSTRIAL COMPONENT DATA

SK U WH:UNGESTANZT 0800129 PHOENIX CONTACT Marker sheet

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK U WH:UNGESTANZT



Manufacturer	PHOENIX CONTACT
MPN / Reference	SK U WH:UNGESTANZT
Catalog number	0800129
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-0AC87BE54C
Generated	2026-11-19

Product Overview

Marker sheet
Identification sheet, DIN A4, white, unlabeled, labelable with: PLOTMARK, CMS-P1-PLOTTER, Office printing systems: without printing, mounting type: glued, for terminal width: 210 mm, useful surface: 296x210mm, Number of individual indexes: 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0800129
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 346 (C-3-2017)
GTIN 4017918005733
Weight per Piece (excluding packing) 15.580 g
Custom tariff number 39199080
Country of origin DE (Germany)
Dimensions
Length (b) 296 mm

Width (a) 210 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 150 °C
Ambient temperature (assembly) > 0 °C
Recommended storage conditions 20-25 °C / 40-50 % relative humidity.
General
Note Print image may vary depending on laser printer
Color white
Type adhesive
Material Polyester
Adhesive Acrylic
Printability Office printing systems
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 50 µm
Adhesive strength 20 µm
Marking mounting type adhesive
Environmental Product Compliance
China RoHS For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classificatio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK U WH:UNGESTANZT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.