INDUSTRIAL COMPONENT DATA

UM5-TM (6X10) 0830919 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM5-TM (6X10)



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM5-TM (6X10)
Catalog number	0830919
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-5C03A9D324
Generated	2026-11-19

Product Overview

Marker for terminal blocks
Markers for labeling terminals of the company Cabur, 20 units, unlabeled, labelable with THERMOMARK CARD and BLUEMARK, color: white
Marker for terminals, Strips, white, unlabeled, labelable with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting class: interlock, for terminal width: 6 mm, Number of individual indexes: 20, text field height: 10 mm, text field width: 6 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0830919
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 181 (C-3-2017)
GTIN 4046356910538
Weight per Piece (excluding packing) 2.220 g
Custom tariff number 39269097

Country of origin PL (Poland)
Dimensions
Length (b) 10 mm
Width (a) 6 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
General
Color white
Type high
Components free from silicone, halogen, and cadmium
Flammability rating according to UL 94 V2
Material PC
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 20
Number of individual labels per row 10
Number of marker strips 2
Printability Thermal transfer
UV LED technology
Device 5146464 THERMOMARK CARD
5147999 BLUEMARK CLED
Ink ribbon 0801371 THERMOMARK-RIBBON 110-TC
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions IEC 61010-1:2010-06
Result Test passed
Marking mounting type clip on
Standards and Regulations
Wipe resistance DIN EN 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM5-TM (6X10) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.