
INDUSTRIAL COMPONENT DATA

UM1-TMF (8X5) YE 0833017 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM1-TMF (8X5) YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM1-TMF (8X5) YE
Catalog number	0833017
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-C031D5106B
Generated	2026-11-19

Product Overview

Marker for terminal blocks
Markers for labeling terminals of the companies Weidmüller, Conta Clip and Klemsan, 14 units, unlabeled, labelable with THERMOMARK CARD and BLUEMARK LED, color: yellow
Markers for marking terminal blocks from Weidmüller, Conta Clip, and Klemsan, 14-section, unmarked, can be marked with THERMOMARK CARD and BLUEMARK, color: yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataProduct propertiesProduct type Terminal marking
Pitch 8 mm
Type flat
Data management status
Article revision 00
Marking
Number of individual labels 14
Number of individual labels per row 7
Number of marker strips 2
DimensionsWidth 5 mm
Length 8 mm

Pitch 8 mm
Material specificationsRoHS compliant yes
Color yellow (RAL 1018)
Material PC
Components free from silicone, halogen, and cadmium
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Wipe resistance of inscriptions
Specification IEC 61010-1:2010-06
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl
[CAS No. 67-63-0] Test passed
n-Hexane
[CAS No. 110-54-3] Test passed
Water + Petroleum ether
[CAS No. 64742-82-1] Test passed
Testing in a condensation changing climate in the presence of sulfur dioxide
Specification DIN 50018:2013-05
Result Test passed
Climate level AHT 1.0 S
Cycles 2
Salt spray test
Specification DIN EN 60068-2-11:2000-02
Result Test passed
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
Standards and regulationsWipe resistance DIN EN 61010-1 (VDE 0411-1)
MountingMounting type snap in

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM1-TMF (8X5) YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.