
INDUSTRIAL COMPONENT DATA

UM1U-TM (5X10) OG 0833031 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM1U-TM (5X10) OG



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM1U-TM (5X10) OG
Catalog number	0833031
Category	Labelling for terminal block
Minimum order	10 Pcs
Document ID	EO-12B8EAB19C
Generated	2026-11-19

Product Overview

Marker for terminal blocks
Markers for labeling terminals of the companies Weidmüller, Conta Clip and Klemsan, 24 units, displaced foot, not labeled, labelable with THERMOMARK CARD and BLUEMARK, color: orange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0833031
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 178 (C-3-2017)
GTIN 4046356984546
Weight per Piece (excluding packing) 2.150 g
Custom tariff number 39269097
Country of origin PL (Poland)
Dimensions
Length (b) 10 mm
Width (a) 5 mm

Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
General
Color orange
Type high
Components free from silicone, halogen, and cadmium
Flammability rating according to UL 94 V2
Material PC
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 24
Number of individual labels per row 12
Number of marker strips 2
Printability Thermal transfer
Device 5146464 THERMOMARK CARD
Ink ribbon 0801371 THERMOMARK-RIBBON 110-TC
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions IEC 61010-1:2010-06
Result Test passed
Marking mounting type clip on
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM1U-TM (5X10) OG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.