INDUSTRIAL COMPONENT DATA

TML (EX10)R 0801839 PHOENIX CONTACT Marking foil for zack marker strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: TML (EX10)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	TML (EX10)R
Catalog number	0801839
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-AF6F15F204
Generated	2026-11-19

Product Overview

Marking foil for zack marker strip
Marking strip, Roll, white, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting class: glued, for terminal width: 30000 mm, useful surface: endless x 10 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0801839
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 155 (C-3-2017)
GTIN 4046356750516
Weight per Piece (excluding packing) 493.400 g
Custom tariff number 39199080
Country of origin DE (Germany)
Dimensions
Length (b) 30000 mm
Width (a) 10 mm

Ambient conditions
Ambient temperature (operation) -40 °C ... 150 °C
Recommended storage conditions 23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing.
General
Color white
Type adhesive
Components free from silicone and halogen
Material Polyester
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 1
Number of individual labels per row 6
Adhesive Acrylic
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146231 THERMOMARK X1.2
Ink ribbon 5145384 THERMOMARK-RIBBON 110
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 53 µm
Adhesive strength 20 µm
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 4.0 241...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TML (EX10)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.