INDUSTRIAL COMPONENT DATA

TML (101X9,5)R TR 0816647 PHOENIX CONTACT Marking foil for zack marker strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: TML (101X9,5)R TR



Manufacturer	PHOENIX CONTACT
MPN / Reference	TML (101X9,5)R TR
Catalog number	0816647
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-144427C88E
Generated	2026-11-18

Product Overview

Marking foil for zack marker strip
Marking strip, Roll, transparent, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting class: glued, for terminal width: 101 mm, useful surface: 101x9.5mm, Number of individual indexes: 1000

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0816647
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 152 (C-3-2017)
GTIN 4046356125529
Weight per Piece (excluding packing) 305.000 g
Custom tariff number 39199080
Country of origin DE (Germany)
Dimensions
Length (b) 101 mm
Width (a) 9.5 mm

Ambient conditions
Ambient temperature (operation) -40 °C ... 150 °C
Recommended storage conditions 10-25 °C / 35-65 % relative humidity. Storage in a cool and dry place is recommended.
General
Color transparent
Type adhesive
Components free from silicone and halogen
Material Polyester
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 1000
Number of individual labels per row 1
Adhesive Acrylic
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 23 µm
Adhesive strength 20 µm
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 4.024190208eCl@ss 4.124190208eCl@ss 5.027149103eCl@ss 5.127141100eCl@ss 6.027149100eCl@ss 7.027149129eCl@ss 8.027141137eCl@ss 9.027141137
ET...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TML (101X9,5)R TR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.