
INDUSTRIAL COMPONENT DATA

FTRV 4 BU/RD 3270174 PHOENIX CONTACT Marshalling panel

Brand: PHOENIX CONTACT | Manufacturer Part Number: FTRV 4 BU/RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	FTRV 4 BU/RD
Catalog number	3270174
Category	Feed-through terminal block
Minimum order	1 Pcs
Document ID	EO-DE811374B6
Generated	2026-11-18

Product Overview

Marshalling panel
Manoeuvring distributor, without drive compressor, rated voltage: 250 V, rated current: 10 A, section: 0.14 mm² - 2.5 mm², AWG: 14 - 26, connection type: Push-in connection, number of poles: 2, number of connections: 16, width: 8.3 mm, length: 64 mm, colour: blue, colour connection elements: red, mounting: NS 35/7.5, NS 35/15
Marshalling panel, without actuating push button, nom. voltage: 250 V, nominal current: 10 A, connection method: Push-in connection, 1st, 2nd, 3rd and 4th level, Rated cross section: 1.5 mm2, cross section: 0.14 mm2 - 2.5 mm2, mounting: NS 35/7,5, NS 35/15, color: blue, color of connection elements: red

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Technical dataProduct propertiesProduct type Marshalling terminal
Number of positions 2
Number of connections 16
Number of rows 4
Potentials 4
Data management status
Article revision 00
Insulation characteristics
Overvoltage category III

Electrical propertiesRated surge voltage 6 kV
Maximum power dissipation for nominal condition 0.56 W
Connection dataNumber of connections per level 4
Nominal cross section 1.5 mm²
1st, 2nd, 3rd and 4th level
Stripping length 8 mm ... 10 mm
Connection in acc. with standard IEC 60947-7-1
Conductor cross section rigid 0.14 mm² ... 2.5 mm²
Cross section AWG 26 ... 14 (converted acc. to IEC)
Conductor cross section flexible 0.14 mm² ... 1.5 mm²
Conductor cross section, flexible [AWG] 26 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 1.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 1.5 mm²
Nominal current 10 A
Maximum load current 10 A (with 1.5 mm² conductor cross section)
Nominal voltage 250 V
Nominal cross section 1.5 mm²
1st, 2nd, 3rd and 4th level Connection cross sections directly pluggable
Conductor cross section rigid 0.34 mm² ... 2.5 mm²
Conductor cross section, rigid [AWG] 20 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.34 mm² ... 1.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.34 mm² ... 1.5 mm²
DimensionsWidth 8.3 mm
Material specificationsColor blue (RAL 5015)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FTRV 4 BU/RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.