INDUSTRIAL COMPONENT DATA

FTMC 1,5/32-3 /BU 3270352 PHOENIX CONTACT Marshalling patchboard

Brand: PHOENIX CONTACT | Manufacturer Part Number: FTMC 1,5/32-3 /BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	FTMC 1,5/32-3 /BU
Catalog number	3270352
Category	Feed-through terminal block
Minimum order	1 Pcs
Document ID	EO-39917AFC99
Generated	2026-11-18

Product Overview

Marshalling patchboard
Sorting honeycomb, 1 - 32 labelling, without drive compressor, rated voltage: 500 V, rated current: 17.5 A, connection type: Push-in connection, cross-section: 0.14 mm² - 2.5 mm², mounting: Wall mounting, colour: grey, connection element colour: blue
Marshalling patchboard, Labeled from 1 - 32, without actuating push button, nom. voltage: 500 V, nominal current: 17.5 A, connection method: Push-in connection, cross section: 0.14 mm2 - 2.5 mm2, mounting: Wall mounting, color: gray, color of connection elements: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Technical dataNotesGeneral Labeled from 1 - 32
Product propertiesProduct type Marshalling terminal
Number of positions 32
Number of connections 192
Number of rows 1
Data management status
Article revision 02
Insulation characteristics
Overvoltage category III

Degree of pollution 3
Electrical propertiesRated surge voltage 6 kV
Maximum power dissipation for nominal condition 0.56 W
Connection dataNumber of connections per level 192
Nominal cross section 1.5 mm²
Rated cross section AWG 14
Stripping length 8 mm ... 10 mm
Internal cylindrical gage A1
Connection in acc. with standard IEC 60947-7-1
Conductor cross section rigid 0.14 mm² ... 2.5 mm²
Cross section AWG 26 ... 14 (converted acc. to IEC)
Conductor cross section flexible 0.14 mm² ... 1.5 mm²
Conductor cross section, flexible [AWG] 26 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 1.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 1.5 mm²
Nominal current 17.5 A
Maximum load current 24 A (in case of a 2.5 mm² conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.)
12 A (in case of a 2.5 mm² conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.)
Nominal voltage 500 V
Connection cross sections directly pluggable
Conductor cross section rigid 0.34 mm² ... 2.5 mm²
Conductor cross section, rigid [AWG] 2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FTMC 1,5/32-3 /BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.