INDUSTRIAL COMPONENT DATA

MBK-FS 1407013 PHOENIX CONTACT Mini feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MBK-FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	MBK-FS
Catalog number	1407013
Category	Feed-through terminal block
Minimum order	1 Pcs
Document ID	EO-5AEBFA3DB7
Generated	2026-11-18

Product Overview

Mini feed-through terminal block
Mini-terminal block, nominal voltage: 400 V, nominal current: 16 A, number of connections: 2, connection type: Screw connection, 1st floor, left-hand connection, cross-section: 0.2 mm² - 2.5 mm², mounting class: NS 15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 1407013
Packing unit 200 pc
Note Made to Order (non-returnable)
Catalog page Page 313 (CL-2005)
GTIN 4017918021054
Weight per Piece (excluding packing) 3.200 g
Custom tariff number 85369010
Country of origin DE (Germany)
General
Number of levels 1
Number of connections 2
Potentials 1

Color gray
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum load current 16 A (with a 2.5 mm² conductor cross section)
Nominal current IN 16 A (current data for slip-on connections in acc. with DIN 61210 are also dependent on nominal size, material, insulation of the sleeve and conductor cross section.)
Nominal voltage UN 400 V (voltage data for slip-on connections in acc. with DIN 61210 are also dependent on nominal size, material, insulation of the sleeve and conductor cross section.)
Open side panel No
Dimensions
Width 4.5 mm
Length 22 mm
Height NS 15 23 mm
Connection data
Connection method Screw connection
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 14
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 1.5 mm²
Min. AWG conductor cross section, flexible 24
Max. AWG conductor cross section, flexible 16
Conductor cross section flexible, with ferrule without...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MBK-FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.