INDUSTRIAL COMPONENT DATA

MC 1,5/10-G-3,5 P26AUTHR 1706431 PHOENIX CONTACT Base housing, rated current: 8 A, number of poles: 10, pitc..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/10-G-3,5 P26AUTHR

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/10-G-3,5 P26AUTHR
Catalog number	1706431
Category	Printed circuit board connector
Minimum order	100 Pcs
Document ID	EO-80C8D00193
Generated	2026-11-19

Product Overview

Base housing, rated current: 8 A, number of poles: 10, pitch: 3.5 mm, color: black, contact surface: Gold, mounting: Solder THR

Printed circuit board base housing, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Male, number of potentials: 10, number of rows: 1, number of poles: 10, number of connections: 10, family of articles: MC 1.5/.. -G-THR, pitch: 3.5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Header, nominal current: 8 A, number of positions: 10, pitch: 3.5 mm, color: black, contact surface: Gold, mounting: THR soldering

Your advantages

Gold-plated contacts ensure transfer quality remains stable over the long termDesigned for integration into the SMT soldering processMaximum flexibility when it comes to device design - one header for connectors with different connection technologiesKey Commercial Data

Orderkey 1706431

Packing unit 1

GTIN 4046356860468

Custom tariff number 85366930
eCl@ss
eCl@ss 4.0 272607xx
eCl@ss 4.1 27260701
eCl@ss 5.0 27260701
eCl@ss 5.1 27260701
eCl@ss 6.0 27260704
eCl@ss 7.0 27440402
eCl@ss 8.0 27440402
eCl@ss 9.0 27440402
ETIM
ETIM 3.0 EC001121
ETIM 5.0 EC002637
ETIM 6.0 EC002637
UNSPSC
UNSPSC 6.01 30211810
UNSPSC 7.0901 39121409
UNSPSC 11 39121409
UNSPSC 12.01 39121409
UNSPSC 13.2 39121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/10-G-3,5 P26AUTHR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.