INDUSTRIAL COMPONENT DATA

HCS-C MINI-P 1W C C C 7035 2203153 PHOENIX CONTACT Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-C MINI-P 1W C C C 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	HCS-C MINI-P 1W C C C 7035
Catalog number	2203153
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-169F0529FE
Generated	2026-11-19

Product Overview

Electronic housing
C-Mini-Plus portable case in light gray, consisting of two halves with screws, 1.1 mm front with reinforcement, with window and keyboard slot
Light grey C-Mini-Plus portable case, consisting of two half-shells with screws, 1.1 mm recessed front, with window and keyboard opening

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203153
Packing unit 1 pc
GTIN 4055626377063
Weight per Piece (excluding packing) 93.000 g
Custom tariff number 39269097
Country of origin DE (Germany)
Item properties
Type HCS-C MINI-P 1W C C C 7035
Order No. 2203153
Housing type Handheld housing

Type straight
Battery compartment no
Measurements
Dimensional drawing
Caption Schematic representation - for additional information, see product range drawing in the Download Center
Width [w] 80 mm
Height [h] 135 mm
Depth [d] 29 mm
Diagonal 2.8 in. (Window for display)
Dimensions 70.4 mm x 69.2 mm x 1.1 mm (Recessed area on front)
70.4 mm x 8.2 mm x 1.1 mm (Recessed area on front)
63 mm x 34 mm (Window for display)
Material specifications
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material ABS
Hammer test
Specification IEC 60068-2-75:2014-09
Impact energy 0.7 J
Number of drop cycles 5
Thermostability (ball thrust test)
Specification IEC 60695-10-2:2014-02
Temperature 80 °C
Test duration 1 h
Force 20
Test for assessing the risk of fire (glow wire)
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Packaging information
Pieces per package 1
Denomination packing units Pcs.
Standards and regulations
Flammability rating according to UL 94 V0
Classifications
eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 5.0EC001031ETIM 6.0EC001031
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSP...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-C MINI-P 1W C C C 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.