INDUSTRIAL COMPONENT DATA

MC 1,5/10-ST-3,5 BS:M250720 1001281 PHOENIX CONTACT Connector for printed circuit board, number of poles: 10..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/10-ST-3,5 BS:M250720



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/10-ST-3,5 BS:M250720
Catalog number	1001281
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-C717BA7092
Generated	2026-11-19

Product Overview

Connector for printed circuit board, number of poles: 10, pitch: 3.5 mm, type of connection: Connection by screw with capsule-wheel drive, color: green, surface contacts: Tin
Connector for printed circuit board, nominal section: 1.5 mm², color: green, rated current: 8 A, sizing voltage (III/2): 160 V, surface contacts: Tin, contact type: Connecting female, Number of potentials: 10, Number of rows: 1, Number of poles per row: 10, number of connections: 10, article family: MC 1.5/.. -ST, pitch: 3.5 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: 0 °, Stecksystem: MINI COMBICON, Lock: without, type of packaging: boxed packaging
PCB connector, nominal cross-section: 1.5 mm2, colour: green, rated current: 8 A, rated voltage (III/2): 160 V, contact surface: tin, contact type: socket, number of potentials: 10, number of rows: 1, number of poles: 10, number of terminals: 10, article family: MC 1,5/.. -ST, Pitch: 3.5 mm, Connection type: Screw connection with pull sleeve, Screw attack shape: L Longitudinal slot, Connection direction conductor/board: 0 °, Plug-in system: COMBICON MC 1.5, Locking: without, Fastening type: without, Packaging type: packed in a carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Connector for printed circuit board, nominal current: 8 A, voltage and sizing (III/2): 160 V, number of poles: 10, pitch: 3.5 mm, type of connection: Connection by screw with capsule-wheel drive, color: green, surface contacts: Tin
Data commercial
Key order One million one thousand two hundred eighty one

Packing unit 50 pcs
Key selling AAAEAA -
Minimum order quantity 50 pcs
EAN Four trillion fifty five billion six hundred twenty six million four hundred sixty nine thousand nine hundred twenty eight
Unit weight (excluding packaging) 7,140 g
Tariff number tariff Eighty five million three hundred sixty six thousand nine hundred ninety
Dimensions
Length [l] 16,1 mm
Width [w] 35 mm
Height [h] 11,1 mm
Step 3.5 mm
Average 31.5 mm
Overview
Family of articles MC 1,5/..-ST
Number of poles Ten
Type of connection Connection by screw with capsule-traction
Nominal cross section 1.5 mm2
Environmental Product Compliance
REACh SVHC
Lead 7439-92-1
China RoHS Space of time for the intended use (FEUP): 50 years
You will find information about hazardous substances in the manufacturer's declaration in the "Downloads"tab
Ratings
eCl@ss
eCl@ss 5.1 Twenty seven million two hundred sixty thousand seven hundred
eCl@ss 6.0 Twenty seven million two hundred sixty thousand seven hundred
eCl@ss 7.0 Twenty seven million four hundred forty thousand three hundred nine
eCl@ss 8.0 Twenty seven million four hundred forty thousand three hundred nine
eCl@ss 9.0 Twenty seven million four hundred forty thousan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/10-ST-3,5 BS:M250720 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.