
INDUSTRIAL COMPONENT DATA

# MCVR 1,5/ 3-ST-3,81 BD:X5-,1-3 1719529 PHOENIX CONTACT Printed-circuit board connector

**Brand: PHOENIX CONTACT | Manufacturer Part Number: MCVR 1,5/ 3-ST-3,81 BD:X5-,1-3**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | MCVR 1,5/ 3-ST-3,81 BD:X5-,1-3 |
| Catalog number | 1719529 |
| Category | Cable connector |
| Minimum order | 50 Pcs |
| Document ID | EO-2E4A1C6E89 |
| Generated | 2026-11-19 |

## Product Overview

Printed-circuit board connector

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Key Commercial Data
Orderkey 1719529
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356141581
Weight per Piece (excluding packing) 2.440 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Length [ l ] 10.4 mm
Width [ w ] 12.22 mm
Height [ h ] 19.1 mm
Pitch 3.81 mm
Dimension a 7.62 mm

General
Range of articles MCVR 1,5/..-ST
Number of positions 3
Connection method Screw connection with tension sleeve
Rated voltage (III/3) 160 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Nominal cross section 1.5 mm²
Connection data
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²
Conductor cross section AWG min. 28
Conductor cross section AWG max. 16
2 conductors with same cross section, solid min. 0.08 mm²
2 conductors with same cross section, solid max. 0.5 mm²
2 conductors with same cross section, stranded min. 0.08 mm²
2 conductors with same cross section, stranded max. 0.75 mm²
2 conductors with same cross section, stranded, ferrules without plastic....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCVR 1,5/ 3-ST-3,81 BD:X5-,1-3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.