INDUSTRIAL COMPONENT DATA

ME MAX 45 F G 3-3 KMGY VPE1 2201330 PHOENIX CONTACT Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME MAX 45 F G 3-3 KMGY VPE1



Manufacturer	PHOENIX CONTACT
MPN / Reference	ME MAX 45 F G 3-3 KMGY VPE1
Catalog number	2201330
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-9920A6F881
Generated	2026-11-19

Product Overview

Electronic housing
Rail box, Full housing with metal pin, 2 screens, 2 transparent covers, flat design, no ventilation slits, width: 45.2 mm, height: 85 mm, depth: 92 mm, color: light gray (Similar RAL 7035), cross bridge: Bus connector for rail (optional), number of poles cross connector: 5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2201330
Packing unit 1 pc
GTIN 4046356767071
Weight per Piece (excluding packing) 64.240 g
Custom tariff number 85389099
Country of origin DE (Germany)
General
Housing type DIN rail housing
Housing material Polyamide
Ambient conditions
Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Dimensions
Width 45 mm
Height 85 mm
Depth 92 mm
Technical data
Connection in acc. with standard CUL
Indicator1 CUL1
Number of positions 36
60
Standards and Regulations
Connection in acc. with standard CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 3.0EC001031ETIM 4.0EC001031ETIM 5.0EC001031ETIM 6.0EC001031
UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC 13.231261501

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME MAX 45 F G 3-3 KMGY VPE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.