INDUSTRIAL COMPONENT DATA

MC 1,5/ 2-ST-3,5 BK BDWH:28,29 1705775 PHOENIX CONTACT Plug-in part, rated current: 8 A, number of poles: 2,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 2-ST-3,5 BK BDWH:28,29

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 2-ST-3,5 BK BDWH:28,29
Catalog number	1705775
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-BD8AD87C9F
Generated	2026-11-18

Product Overview

Plug-in part, rated current: 8 A, number of poles: 2, pitch: 3.5 mm, connection type: Screw connection with traction capsule, color: black, contact surface: Tin

Connector for printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: MC 1.5/.. -ST, pitch: 3.5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Plug component, nominal current: 8 A, number of positions: 2, pitch: 3.5 mm, connection method: Screw connection with tension sleeve, color: black, contact surface: Tin

Your advantages

Well-known connection principle allows worldwide useLow temperature rise, thanks to maximum contact forceAllows connection of two conductorsKey Commercial Data

Orderkey 1705775

Packing unit 1

GTIN 4046356801003
Custom tariff number 85366990
General
Range of articles MC 1,5/..-ST
Type of contact Female connector
Number of positions 2
Connection method Screw connection with tension sleeve
Rated voltage (III/3) 160 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Nominal cross section 1.5 mm²
Connection data
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²
Conductor cross section AWG min. 28
Conductor cross section AWG max. 16
2 conductors with same cross section, solid min. 0.08 mm²
2 conductors with same cross section, solid max. 0.5 mm²
2 conductors with same cross section, stranded min. 0.08 mm²
2 conductors with same cross se...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 2-ST-3,5 BK BDWH:28,29 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.