INDUSTRIAL COMPONENT DATA

MC 1,5/ 3-ST-3,81GY7035BD14-12 1702581 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 3-ST-3,81GY7035BD14-12



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 3-ST-3,81GY7035BD14-12
Catalog number	1702581
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-029E4E201A
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 1.5 mm², color: light gray, nominal current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Tin, contact type: Female connection, Number of potentials: 3, Number of rows: 1, Number of poles per row: 3, number of connections: 3, family of articles: MC 1.5/.. -ST, pitch: 3.81 mm, connection type: Screw connection with traction capsule, conductor connection direction/printed circuit board: 0 °, Stecksystem: MINI COMBICON, Lock: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1702581
Packing unit 1
GTIN 4046356593014
Custom tariff number 85366990
Dimensions
Length [l] 16.1 mm
Width [w] 12.22 mm
Height [h] 11.1 mm
Pitch 3.81 mm

Dimension a 7.62 mm
General
Range of articles MC 1,5/..-ST
Number of positions 3
Connection method Screw connection with tension sleeve
Rated voltage (III/3) 160 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Nominal cross section 1.5 mm²
Connection data
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²
Conductor cross section AWG min. 28
Conductor cross section AWG max. 16
2 conductors with same cross section, solid min. 0.08 mm²
2 conductors with same cross section, solid max. 0.5 mm²
2 conductors with same cross section, stranded min. 0.08 mm²
2 conductors with same cross section, stranded max. 0.75 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 0.34 mm²
2 conductors with same cross s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 3-ST-3,81GY7035BD14-12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.