INDUSTRIAL COMPONENT DATA

# MC 1,5/ 4-G-3,81 GY 1852639 PHOENIX CONTACT Printed-circuit board connector

**Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 4-G-3,81 GY**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | MC 1,5/ 4-G-3,81 GY |
| Catalog number | 1852639 |
| Category | Printed circuit board connector |
| Minimum order | 250 Pcs |
| Document ID | EO-0C628B1B06 |
| Generated | 2026-11-19 |

## Product Overview

Printed-circuit board connector
Printed circuit board base case, nominal section: 1.5 mm², color: gray, nominal current: 8 A, contact surface: Tin, contact connection type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: MC 1.5/.. -G, pitch: 3.81 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, locking: without, packaging type: boxed

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Key Commercial Data
Orderkey 1852639
Packing unit 50 pc
Minimum order quantity 50 pc
GTIN 4017918264727
Weight per Piece (excluding packing) 1.080 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Length [ l ] 9.2 mm

Width 16.63 mm
Pitch 3.81 mm
Dimension a 11.43 mm
Width [ w ] 16.63 mm
Height [ h ] 10.65 mm
Height 7.25 mm
Length of the solder pin 3.4 mm
Pin dimensions 0.8 x 0.8 mm
Length 9.2 mm
General
Range of articles MC 1,5/..-G
Rated voltage (III/3) 160 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Color gray
Number of positions 4
Standards and Regulations
Connection in acc. with standard EN-VDE
CSA
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 4-G-3,81 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.