INDUSTRIAL COMPONENT DATA

HCS-C MINI-P 1W 2AA C C 7035 2203157 PHOENIX CONTACT Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-C MINI-P 1W 2AA C C 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	HCS-C MINI-P 1W 2AA C C 7035
Catalog number	2203157
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-39949087A0
Generated	2026-11-19

Product Overview

Electronic housing
C-Mini-Plus portable case in light gray, formed by two halves, screws. Front with 1.1 mm reinforcement, with window and keyboard slot, battery compartment cover and battery contacts for 2 AA batteries

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203157
Packing unit 1 pc
GTIN 4055626377094
Weight per Piece (excluding packing) 93.000 g
Custom tariff number 39269097
Country of origin DE (Germany)
Item properties
Type HCS-C MINI-P 1W 2AA C C 7035
Order No. 2203157
Housing type Handheld housing
Type straight
Battery compartment 2 x AA

Measurements
Dimensional drawing
Caption Schematic representation - for additional information, see product range drawing in the Download Center
Width [w] 80 mm
Height [h] 135 mm
Depth [d] 29 mm
Diagonal 2.8 in. (Window for display)
Dimensions 70.4 mm x 69.2 mm x 1.1 mm (Recessed area on front)
70.4 mm x 8.2 mm x 1.1 mm (Recessed area on front)
63 mm x 34 mm (Window for display)
Material specifications
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material ABS
Hammer test
Specification IEC 60068-2-75:2014-09
Impact energy 0.7 J
Number of drop cycles 5
Thermostability (ball thrust test)
Specification IEC 60695-10-2:2014-02
Temperature 80 °C
Test duration 1 h
Force 20
Test for assessing the risk of fire (glow wire)
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Packaging information
Pieces per package 1
Denomination packing units Pcs.
Standards and regulations
Flammability rating according to UL 94 V0
Classifications
eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702
ETIM 5.0EC001031ETIM 6.0EC001031
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 11391214...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-C MINI-P 1W 2AA C C 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.